

Porous Stone Sealer Solvent Based

FILAFOB

SEALER
SOLVENT BASED

FILA®
surface care solutions

POROUS UNPOLISHED NATURAL STONE, CONCRETE, TERRACOTTA AND QUARRY TILE



- POROUS STONE SEALER.
- SUITABLE FOR HONED MARBLE, LIMESTONE AND TRAVERTINE.



Coverage:

1 QT (0.95 L)

Porous natural stone (marble, granite, limestone, sandstone and travertine)

› 108-215 sq.ft. (10-20 m²)

Terracotta (Tuscan, rustic, polished, handmade terracotta and concrete)

› 161-215 sq.ft. (5-20 m²)

Coverage rates are indicative and per coat.



Packaging:

1 QT (946 ml) 5 plastic bottles per box

5 L (1.32 GAL) 4 plastic bottles per box

WHAT IT'S FOR

- Natural look, penetrating sealer that protects porous, unpolished natural stone, concrete, terracotta and quarry tile against stains.
- Forms an invisible, protective barrier resistant to moisture and stains while allowing water vapor to escape.
- Suitable for indoor and outdoor surfaces.
- Ideal for the treatment of concrete and quarry tile.
- Perfect for honed marble, limestone and travertine.

ADVANTAGES

- Long lasting protection.
- Does not yellow or discolor over time.
- UV resistant.
- Certified safe in food preparation areas.
- Does not alter the frost resistance of terracotta.
- PFOA free: non carcinogenic.

HOW TO USE IT

Ready to use, no dilution necessary.

Instructions:

Outdoor surfaces: On a clean and dry surface, first apply a coat of **HYDROREP** as a primer. The following day, apply **FILAFOB** with a large paint brush or roller. Wait 24 hours before use.

Alternatively: Apply two coats of **FILAFOB** allowing for 24 hours between coats.

Indoor surfaces: Apply **FILAFOB** with a large paint brush or roller. Wait 24 hours and apply a second coat as indicated above. After 24 hours, the treatment may be completed with one or two coats of an appropriate **FILA** wax (**FILAMATT**, **FILASATIN**).

Caution: Do not apply **FILAFOB** on a previously waxed surface. Before full application, test the product on a small, inconspicuous area of the surface or loose sample to check for any discoloration. Do not apply **FILAFOB** outdoors if rain is in the forecast.

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS

manufacturers of materials for floors and wall coverings

usa.filasolutions.com